


















FLACHSTECKKONTAKTE/FLACHSTECKER DIVERSE

* für Einzelleitungs-dichtungen (Seals)

	mm ²	Isol.-Ø mm	Seal-Ø mm	Stecker mm	Rast- zunge	Werkstoff	Oberfläche	Art.-Nr.	VE/St.
	0,5-1,0	1,2-2,1	3,40	1,5 x 0,8	1 x	CuZn	Sn (verzinnt)	0558 995 4*	100
	0,5-1,0	1,2-2,1	-	1,5	1 x	CuSn		0558 190 34	
	0,5-1,0	1,2-2,1	3,40	1,5	1 x	CuSn		0558 995 41*	
	0,35-0,5	1,2-1,6	3,40	1,5	-	CuSn	Sn (verzinnt)	0558 995 80*	
	0,75-1,5	1,7-2,4	3,40	1,5	-			0558 995 82*	
	1,5-2,5	2,2-3,3	3,40	1,5	-			0558 995 84*	
	0,35-0,5	1,2-1,6	3,40	1,5 x 0,8	-	CuZn	Sn (verzinnt)	0558 995 79*	
	0,75-1,5	1,7-2,4	3,40	1,5 x 0,8	-			0558 995 81*	
	1,5-2,5	2,2-3,3	3,40	1,5 x 0,8	-			0558 995 83*	
	0,5-1,25	2,0-2,6	-	1,7	-	CuZn	Sn (verzinnt)	0558 190 36	
	0,5-1,25	2,0-2,6	-	1,7 x 0,65	-			0558 190 41	
	0,5-1,25	2,0-2,6	2,90	1,7	-			0558 190 35*	
	0,5-1,25	2,0-2,6	2,90	1,7 x 0,65	-			0558 190 42*	
	0,5-1,25	1,6-2,5	-	2,3	-	CuZn	Sn (verzinnt)	0558 190 33	
	0,5-1,25	1,6-2,9	-	2,3 x 0,65	-			0558 190 40	
	0,35-0,75	1,5-2,6	-	3,0	-	CuZn	Sn (verzinnt)	0558 190 310	
	0,75-1,75	2,1-3,4	-	3,0	-			0558 190 311	
	0,35-0,75	1,5-2,6	-	3,0 x 0,65	-			0558 995 74	
	0,75-1,75	2,2-3,4	-	3,0 x 0,65	-			0558 995 75	
	0,5-1,0	1,4-2,3	-	2,8 x 0,8	1 x	CuSn	Sn (verzinnt)	0558 995 70	
	1,5-2,5	2,3-3,5	-	2,8 x 0,8	1 x			0558 995 71	
	0,5-1,0	-	-	2,8 x 0,8	1 x			0558 992 4	
	0,5-1,0	1,2-2,1	3,40	2,8 x 0,8	1 x			0558 995 8*	
	1,0-2,5	1,9-3,0	6,00	4,8 x 0,8	1 x			0558 994 5*	

ORSY®-lagerfähig

Zusatzartikel:

Entriegelungswerkzeug

Art.-Nr. 0713 558 2..

Entriegelungswerkzeug für Art.-Nr. 0558 190 56

Art.-Nr. 0713 558 342, 0713 558 343

Einzelleitungs-dichtungen

Art.-Nr. 0558 991 4..