











LASTBOCK MIT UNVERLIEBbarer SCHRAUBE

Art.-Nr.	Gewindeart x Nenn-durchmesser	Tragfähigkeit max.											Drehmoment max.
			0°	0°	90°	90°	0-45°	45-60°	Asymm	0-45°	45-60°	Asymm	
		W.L.L.	1 Strang	2 Stränge	1 Strang	2 Stränge	2 Stränge		Asymm	3/4 Stränge		Asymm	
5162 114 8	M8	0,3 †	0,3	0,6	0,3	0,6	0,42	0,3	0,3	0,63	0,45	0,3	30 Nm
5162 114 10	M10	0,63 †	0,63	1,26	0,63	1,26	0,88	0,63	0,63	1,32	0,95	0,63	60 Nm
5162 114 12	M12	1 †	1	2	1	2	1,4	1	1	2,1	1,5	1	100 Nm
5162 114 16	M16	1,5 †	1,5	3	1,5	3	2,1	1,5	1,5	3,15	2,25	1,5	150 Nm
5162 114 20	M20	2,5 †	2,5	5	2,5	5	3,5	2,5	2,5	5,25	3,75	2,5	250 Nm
5162 114 24	M24	4 †	4	8	4	8	5,6	4	4	8,4	6	4	400 Nm
5162 114 27	M27	4 †	4	8	4	8	5,6	4	4	8,4	6	4	400 Nm
5162 114 30	M30	5 †	5	10	5	10	7	5	5	10,5	7,5	5	500 Nm
5162 114 36	M36	7 †	7	14	7	14	9,8	7	7	14,7	10,4	7	700 Nm
5162 114 361	M36	8 †	8	16	8	16	11,2	8	8	16,8	12	8	800 Nm
5162 114 42	M42	10 †	10	20	10	20	14	10	10	21	15	10	925 Nm
5162 114 421	M42	15 †	15	30	15	30	21	15	15	31,5	22,5	15	1500 Nm
5162 114 48	M48	20 †	20	40	20	40	28	20	20	42	30	20	2000 Nm