


X
Phi



Basic setup

	1	2	3	4	5	6	7	8
	Basic 2000 lm	Basic 2000 lm	Basic 2000 lm	Basic 2000 lm	Basic 2000 lm	Basic 2000 lm	Basic 2000 lm	Basic 2000 lm
tilt°	-20°	-20°	-35°	-35°	-15°	-15°	-15°	-15°
phi°	0°	15°	0°	0°	90°	-90°	165°	-165°



LAMPS USED

Nordic Lights SETUP 1.



Canis Pro 415
PH

or



Scorpius Pro 415 PH



Pictor 620



Scorpius Pro
445



Nordic Lights SETUP 1.

	1	2	3	4	5	6	7	8	9	10	11	12	13	14
	Scorpius Pro 445 WideFloored Asymmetric	Scorpius Pro 445 WideFloored Asymmetric	Scorpius Pro 445 WideFloored Asymmetric	Scorpius Pro 445 WideFloored Asymmetric	Scorpius Pro 445 WideFloored Asymmetric	Scorpius Pro 445 WideFloored Asymmetric	Pictor 620	Pictor 620	Pictor 620	Canis/Scorpius Pro 415 PH	Canis/Scorpius Pro 415 PH	Canis/Scorpius Pro 415 PH	Canis/Scorpius Pro 415 PH	Canis/Scorpius Pro 415 PH
tilt°	-10°	-20°	-20°	-20°	-20°	-10°	-35°	-35°	0°	0°	0°	0°	0°	0°
phi°	0°	10°	30°	55°	80°	-30°	0°	0°	0°	-70°	110°	-110°	160°	-160°

VEHICLES





